

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 1: IDENTIFICATION

1.1 GHS Product identifier: Kolor Xtreme Liquid Resin

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses: Car repair; filler for joints, cracks, etc...

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:

Troton Sp. z o.o.

Ząbrowo 14A

78-120 Gościno - Zachodniopomorskie - Polska

Phone.: +48 94 35 123 94 - Fax: +48 94 35 126 22

troton@troton.com.pl

www.troton.pl

1.4 Emergency phone number: CHEMTREC 24h: 1-800-424-9300 / +1 703-527-3887

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture:

29 CFR 1910.1200:

Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.

Carc. 2: Carcinogenicity, Category 2, H351

Eye Irrit. 2: Eye irritation, Category 2, H319

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

2.2 Label elements:

29 CFR 1910.1200:

Warning



Hazard statements:

Carc. 2: H351 - Suspected of causing cancer

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 3: H226 - Flammable liquid and vapour

Skin Irrit. 2: H315 - Causes skin irritation

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P264: Wash thoroughly after use

P280: Wear protective gloves/protective clothing/eye protection/face protection

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P370+P378: In case of fire: Use ABC powder extinguisher to put it out

P501: Dispose of contents and / or their container according to the separated collection system used in your municipality

Substances that contribute to the classification

Styrene Monomer

2.3 Hazards not otherwise classified (HNOC):

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019


Version: 4 (Replaced 3)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Chemical description: Mixture composed of chemical products

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

| Identification | Chemical name/Classification | Concentration |
|----------------|---|--|
| CAS: 100-42-5 | Styrene Monomer Acute Tox. 4: H332; Aquatic Acute 2: H401; Carc. 2: H351; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315 - Warning |  25 - <50 % |

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertization agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

The characteristic of Ignitability per RCRA could apply to the unused product if it becomes a waste material. The EPA hazardous waste number D001 could apply. It is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing.

6.3 Methods and materials for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Because the product is a flammable liquid, storage should meet the requirement of 29 CFR 1910.106, Flammable and Combustible Liquids Code. Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 59 °F
Maximum Temp.: 77 °F
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)


| Identification | Environmental limits | | |
|-----------------|--------------------------|---------|--|
| Styrene Monomer | 8-hour TWA PEL | 100 ppm | |
| CAS: 100-42-5 | Ceiling Values - TWA PEL | 200 ppm | |

8.2 Appropriate engineering controls:


A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection


| Pictogram | PPE | Remarks |
|---|---------------------------------------|--|
|  Mandatory respiratory tract protection | Filter mask for gases and vapours (A) | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands



| Pictogram | PPE | Remarks |
|--|--|--|
|  Mandatory hand protection | NON-disposable chemical protective gloves (NBR), Breakthrough Time 480 min, thickness 0.4 mm | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR) |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application



D.- Ocular and facial protection

| Pictogram | PPE | Remarks |
|--|---|---|
|  Mandatory face protection | Panoramic glasses against splash/projections. | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR) |

E.- Bodily protection

| Pictogram | PPE | Remarks |
|---|---|---|
|  Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | For professional use only. Clean periodically according to the manufacturer's instructions. |
|  Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

National volatile organic compound emission standards (40 CFR Part 59):

| | |
|--------------------------------|---------------------------------|
| V.O.C. (Subpart C - Consumer): | 45 % weight |
| V.O.C. (Coatings) at 68 °F: | 855 kg/m ³ (855 g/L) |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|--|
| Physical state at 68 °F: | Liquid |
| Appearance: | Fluid |
| Color: |  Yellow |
| Odor: | Characteristic |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|----------------------|
| Boiling point at atmospheric pressure: | 293 °F |
| Vapour pressure at 68 °F: | 622 Pa |
| Vapour pressure at 122 °F: | 3297.17 Pa (3.3 kPa) |
| Evaporation rate at 68 °F: | Non-applicable * |

Product description:

| | |
|--|------------------------|
| Density at 68 °F: | 1900 kg/m ³ |
| Relative density at 68 °F: | Non-applicable * |
| Dynamic viscosity at 68 °F: | -3400 - 3600 cP |
| Kinematic viscosity at 68 °F: | Non-applicable * |
| Kinematic viscosity at 104 °F: | Non-applicable * |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 68 °F: | Non-applicable * |
| Partition coefficient n-octanol/water 68 °F: | Non-applicable * |
| Solubility in water at 68 °F: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |

Flammability:

| | |
|----------------------------|------------------|
| Flash Point: | 90 °F |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 914 °F |
| Lower flammability limit: | Not available |
| Upper flammability limit: | Not available |

Explosive:

| | |
|------------------------|------------------|
| Lower explosive limit: | Non-applicable * |
|------------------------|------------------|

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 68 °F: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
- IARC: Styrene Monomer (2A)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|----------------------------------|-----------------|---------------|-------|
| Styrene Monomer CAS: 100-42-5 | LD50 oral | >5000 mg/kg | |
| | LD50 dermal | >5000 mg/kg | |
| | LC50 inhalation | 12 mg/L (4 h) | Rat |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Ecotoxicity (aquatic and terrestrial, where available):

| Identification | Acute toxicity | | Species | Genus |
|----------------------------------|----------------|--------------------|---------|------------|
| Styrene Monomer CAS: 100-42-5 | LC50 | 1 - 10 mg/L (96 h) | | Fish |
| | EC50 | 1 - 10 mg/L | | Crustacean |
| | EC50 | 1 - 10 mg/L | | Algae |

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

Not available

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|----------------------------------|-----------------------|---------------------|------------|----------------|
| Styrene Monomer CAS: 100-42-5 | Koc | Non-applicable | Henry | Non-applicable |
| | Conclusion | Non-applicable | Dry soil | Non-applicable |
| | Surface tension | 3.21E-2 N/m (77 °F) | Moist soil | Non-applicable |

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

- CONTINUED ON NEXT PAGE -

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See epigraph 6.2.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Part 261- IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



- | | |
|--|---|
| 14.1 UN number: | UN3269 |
| 14.2 UN proper shipping name: | POLYESTER RESIN KIT, liquid base material |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | 3 |
| 14.4 Packing group, if applicable: | III |
| 14.5 Marine pollutant: | No |
| 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises | |
| Physico-Chemical properties: | see section 9 |
| 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): | Non-applicable |

Transport of dangerous goods by sea:

With regard to IMDG 38-16:



- | | |
|--|---|
| 14.1 UN number: | UN3269 |
| 14.2 UN proper shipping name: | POLYESTER RESIN KIT, liquid base material |
| 14.3 Transport hazard class(es): | 3 |
| Labels: | 3 |
| 14.4 Packing group, if applicable: | III |
| 14.5 Marine pollutant: | No |
| 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises | |
| Physico-Chemical properties: | see section 9 |
| 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): | Non-applicable |

Transport of dangerous goods by air:

With regard to IATA/ICAO 2020:

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN3269
14.2 UN proper shipping name: POLYESTER RESIN KIT, liquid base material
14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group, if applicable: III
14.5 Marine pollutant: No
14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises
Physico-Chemical properties: see section 9
14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

SARA Title III - Toxic Chemical Release Inventory Reporting (Section 313): Styrene Monomer
California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986): Styrene Monomer
The Toxic Substances Control Act (TSCA) : Styrene Monomer
Massachusetts RTK - Substance List: Styrene Monomer
New Jersey Worker and Community Right-to-Know Act: Styrene Monomer
New York RTK - Substance list: Styrene Monomer
Pennsylvania Worker and Community Right-to-Know Law: Styrene Monomer
CANADA-Domestic Substances List (DSL): Styrene Monomer
CANADA-Non-Domestic Substances List (NDSL): Non-applicable
NTP (National Toxicology Program): Styrene Monomer
Minnesota - Hazardous substances ERTK: Styrene Monomer
Rhode Island - Hazardous substances RTK: Styrene Monomer
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable
Hazardous substances release notification under CERCLA sections 102-103 (40 CFR Part 302): Styrene Monomer (1000 pounds)

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The Toxic Substances Control Act (TSCA)
Occupational Safety and Health Standards (1910 Subpart Z - Toxic and Hazardous Substances)

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation
H351: Suspected of causing cancer
H226: Flammable liquid and vapour
H319: Causes serious eye irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

29 CFR 1910.1200:

Acute Tox. 4: H332 - Harmful if inhaled
Aquatic Acute 2: H401 - Toxic to aquatic life
Carc. 2: H351 - Suspected of causing cancer
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Liq. 3: H226 - Flammable liquid and vapour
Skin Irrit. 2: H315 - Causes skin irritation

Advice related to training:

- CONTINUED ON NEXT PAGE -

Kolor Xtreme Liquid Resin

Printing: 2/18/2020

Date of compilation: 6/27/2011

Revised: 8/26/2019

Version: 4 (Replaced 3)

SECTION 16: OTHER INFORMATION (continued)

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET